

## TRW SPS (TYPE 2A/DISCO II) - System Overview

Fitted exclusively in the Discovery series II from introduction, this system supports side Airbags and Seat Belt Pretensioners. It is a close relative of the SPS type 2 and also supports the option of additional external crash sensors.



## TRW SPS (TYPE 2A/DISCO II) - Known Fitments

Vehicle makes models and variants known or believed to be using this vehicle system, required diagnostic lead and degree of known compatibility.

Vehicle Make	Vehicle Model	Vehicle Variant	Diagnostic lead	Compatibility Level
Land Rover	Discovery II	All	Blue OBD lead	Verified
Land Rover	Discovery II	All	Green OBD Lead	Verified

## TRW SPS (TYPE 2A/DISCO II - Pin Outs)

1 - 2	Driver's airbag via rotary coupler
3 - 4	Passenger's airbag
5	Not used
6 - 7	RH Pretensioner

8	Not used
9	Diagnostic socket
10 - 11	LH Pretensioner
12	Not used
13	Warning lamp
14	Ground
15	Passenger compartment fuse box
16 - 30	Not Used

### TRW SPS (TYPE 2A/DISCO II) - Diagnostic Capabilities - Read Fault Codes/ Clear Fault Codes

Each airbag system can self detect up to 37 faults. Most of these are major or safety related faults causing full system shutdown with only a few being minor caused by, for instance a flat battery. The systems perform a self-diagnostic test that takes about 15 seconds whenever the ignition is switched on, logging any faults that are found, and then at regular intervals thereafter.

Resistors are placed at strategic points in the airbag wiring harness / loom giving the systems the ability to self detect open or short circuits. Main loom loops are from the ECU up the column through the spiral cassette through the airbag and back through the spiral cassette to the ECU; from the ECU through the passenger airbag and back again; on MPS systems, one through each of the two crash sensors mounted behind the head lamps at the front and then returning to the ECU, and then two loops each going to the instrument cluster, through a bulb each and back again. In accordance with the manuals no repairs must be carried out on the loom at all, hence no wiring diagram is supplied in the manufacturer's manuals. All problems involving the airbags, spiral cassette, crash sensors, or loom must be done in strict accordance with the relevant manufacturer's workshop manual instructions. There is a deep memory within the airbag ECU that keeps a long-term record of resets to detected faults. This means that if a particular connection was poor and went open circuit - even just once - the fault would be logged by the system as - a sensor is open circuit - and the airbag warning light would come on. If the fault was not found and the fault code memory was cleared it would be very likely to reappear. This would be logged as an intermittent fault within the system.

The Clear Fault Code function checks the fault code memory for resident faults and clears the fault code memory if the fault has been rectified. Having deleted the faults the system then rechecks the fault memory to ensure that it is clear. Failure to clear the fault memory successfully is usually due to the system re-logging the fault the moment the fault memory is clear, meaning that the fault has not been rectified properly and as far as the system is concerned, still exists. The system may also carry out a re-check for successful clearing of the fault code memory but then the system may re-log the fault shortly after.

### TRW SPS (TYPE 2A/DISCO II) - Diagnostic Capabilities (Settings)

Values, configuration settings, and other stored information which can be read from the ECU, edited and then rewritten back. Read settings can also be stored as a standard HTML page for reference. These pages can then later be re loaded and re written back to the ECU. Please note that some values may be read only due to the fact that they are supplied from the ECU's ROM or are internally calculated.

- Manufacturer: Gives the manufacturer's name for the airbag ECU.
- Model: Gives the manufacturer's model code allocated to this airbag ECU. Not all ECU types feature this information diagnostically.
- Software version: Gives the software version number for this airbag ECU. Not all ECU types feature this information diagnostically.
- Hardware version: Gives the hardware version number for this airbag ECU. Not all ECU types feature this information diagnostically.
- Serial number: The electronically stored serial number for this airbag ECU, and can be found printed on a label affixed to the top or side of the ECU.
- Date of build: Gives the electronically stored date of build for this airbag ECU. Not all ECU types feature this information diagnostically.
- Part reference: Gives the part reference which identifies the family variant of this airbag ECU. Not all ECU types feature this information diagnostically.
- Part number: Gives the vehicle part number for this airbag ECU. Not all ECU types feature this information diagnostically.

**The SRS airbag has only one programmable option:**

- VIN: The electronically stored Vehicle Identification Number (VIN) in this airbag ECU. This number should be changed if the ECU is fitted in another vehicle. It should also be entered on new airbag ECU's. The number can be found on the VIN plate under the bonnet or on the visible VIN tag at the bottom of the windscreen.
- Driver's airbag/ Passenger's airbag: This denotes fitment or omission of the driver's/passenger's airbag. Not all ECU types feature this information diagnostically.
- Right hand Pretensioner/ Left hand Pretensioner: This denotes fitment or omission of the right hand/left hand seat belt Pretensioner. Not all ECU types feature this information diagnostically.
- Driver's side airbag / Passenger's side airbag: This denotes fitment or omission of the driver's/passenger's side airbag. Not all ECU types feature this information diagnostically.
- Rolamites: